



Mastercool[®] Inc.
"World Class Quality"

1 ASPEN DRIVE, RANDOLPH, NJ 07869
PHONE: 973-252-9119 / FAX: 973-252-2455
WEB: WWW.MASTERCOOL.COM

55745 ***Black Series*** INFRARED CO₂ LEAK DETECTOR



SPECIFICATIONS:

- Sensor life: 40,000 hours
- Sensitivity:
High < 350 ppm at 350 ppm ambient
Low < 3500 ppm at 350 ppm ambient
- Alarm mode: visual and audible
- Display: high resolution bright TFT active matrix LCD
- Automatic shutdown:
10 minutes without operation
- Reset time: <3 seconds
- Warm-up time: 30 seconds
- Response time: <1 second
- Refrigerants: R744 (CO₂)
- Battery: rechargeable (8 hours of detection)
- Storage temperature: -20 to 60°C (-4 to 140°F)
- Operating temperature: -10 to 52°C (14 to 125.6°F)
- Humidity: maximum 90% RH (non-condensing)
- Probe length: 14.37"
- Weight: 15 oz.
- Size: 7.8 x 3 x 1.5"

EXTREMELY EFFECTIVE AT LOCATING CO₂ LEAKS

Mastercool's 55745 handheld CO₂ leak detector uses an advanced infrared sensor to effectively pinpoint R744 (CO₂). The efficient design and rugged construction provides effortless leak detection all while allowing the technician to easily adjust sensitivity to adapt to different environments.

Packaged in a zippered carry case, this kit includes the 55745 infrared CO₂ leak detector, charging cable and replacement filters.

FEATURES:

- Flexible probe is easy to use and extremely effective at locating difficult leaks
- Advanced infrared sensor with a sensor life of 40,000 hours
- Easily select high, medium and low sensitivity levels
- Advanced TFT screen provides clear and easy readings using color graphics that show leakage, sensitivity, battery level and sensor fault indicators
- Peak button indicates the maximum leak detected during measurements
- Auto-off function will automatically shut down the unit after 10 minutes
- Compliant to RoHS, SAE-J1627 and EN14624

